

Temperature and Humidity Monitor



An AIoT device using LPWAN transmission. It stands out for its ease of installation, low power consumption, and high accuracy. Offering real-time comprehensive environmental monitoring information to businesses and includes alert functions, enabling users to immediately detect any abnormal environmental conditions and take necessary actions.

EASY TO IMPLEMENT!
COST-EFFECTIVE!
HIGH PERFORMANCE!



Simple to Install

No extra internet connection required. Resistance to dust and moisture. Installation in few seconds.

7/24 Monitoring

Mobile & Web APP supported. Installation in few seconds. Instant Alert / Notification.

Digital Transformation

Automatic Temperature and Humidity Value record. Easily report generating.

Awesome Deal

Affordable Price. Zero cost for reconstruction works on your site.

TEMPHAWK DEVICE



IP68 water/dust proof
 Reliable in all environments.



Plug and play
 Plug sensor in and go.



High-accuracy sensor
 Temperature Range: -40°C ~ 120 °C.
 Humidity Range: 0 ~ 100%.
 Frequency: 10 min. SGS Certified.

TEMPHAWK CLOUD



Chart and data records
 Intuitive chart and graph. PDF, CSV, EXCEL report supported.



Multiple language
 Chinese, English, Japanese... etc supported.



API
 Standard API portal for other system integration.

TEMPHAWK MOBILE APP



Push notification
 Abnormal value, device disconnecting alert. Free to define alert conditions.



Device group
 Manage devices with ease by grouping.



Cloud storage
 Access historical data anytime and anywhere.

